

INSTALLATION INSTRUCTION FOR FRIEZES & DECORATIONS

PLEASE READ ALL THE
INSTRUCTIONS BEFORE
STARTING THE
INSTALLATION PROCEDURE

(Recommended by us and guaranteed our product)

BEFORE LAYING

The friezes and decorations must be acclimatized to the temperature of the place of installation.

- 1 - Lower the water level by 50 cm for the friezes.
- 2 - Empty pool water for background decorations.

The surface (s) must be degreased (s) (DEG 11* grease-removing)
And perfectly clean before proceeding the installation.

Remove all dirt and other residue with an alcohol-based cleaner
(Alcohol, isopropanol).

TEMPERATURE DURING INSTALLATION: Climatic condition / temperatures between 15 ° and 22 °.

make sure you have :

Scraper* - Sprayer **EASY POSE*** - Tape Measure - Box Cutter or Scalpel - Clean cloth
Masking adhesive.



LAYING

- Begin laying preferably in an angle.
- Spray with **Easy Pose (réf DEG 12*)** on the surface.
- Turn over the frieze or decoration and remove the silicone paper that protects the adhesive side
- Take the frieze or decoration and lay it on the surface.
- Slide the frieze or decoration and position it very precisely.
- Take the squeegee, chase the liquid from the middle outwards high then down.
- Avoid the formation of air bubbles during bonding.
- Do not puncture air bubbles to avoid damaging the frieze and liner.
- Once the liquid has completely disappeared, the adhesive side of the frieze or decoration adheres and is fixed to the support.
Drying time 48 hours, with a recommended temperature between 15 ° and 22 °.
- After placing the frieze, it is preferable to apply a PVC seal on the edges to the corners and around the skimmers in order to obtain a perfect seal.
- For decorations, apply a PVC seal around the edges.



For sale on our site (joint MS texton CCPRO Hm 290 ml).

After 48 hours of drying time, raise your water level.

ANGLES / CURVES : Cut vertically into corners.

EDGE CUTTING : To avoid damaging the liner use the supplied PVC support*
to protect your liner.

MAINTENANCE : The water temperature of the basin must not exceed 30 °.

